SAFETY DATA SHEET

1. Identification

Product number	AUS012
Product identifier	11 OZ ULTRA SIL LB 12PK - AUS012
Revision date	06-10-2015
Company information	Pro-Line Industrial Products
	NEXGEN
	PO Box 401,
	Dixon, CA 95620 United States
Company phone	General Assistance 800-263-9436
Emergency telephone US	1-800-424-9300
Emergency telephone outside US	1-952-852-4646
Version #	04
Supersedes date	06-07-2015
Recommended use	Lubricant
Recommended restrictions	None known.
2. Hazard(s) identification	
Physical hazards	Flammable aerosols
Health hazards	Aspiration hazard
Environmental hazards	Not classified.
OSHA defined hazards	Not classified.

Label elements

Category 1 Category 1

Signal word	Danger
Hazard statement	Extremely flammable aerosol. May be fatal if swallowed and enters airways.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.
Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.
Storage	Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Not available.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	40 - 60
Propane		74-98-6	20 - 40
Odorless Mineral Spirits		64741-65-7	10 - 20
Polydimethylsiloxane		63148-62-9	2.5 - 10

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Rinse skin with water/shower.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do.
Ingestion	Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately.
5. Fire-fighting measures	
Suitable extinguishing modia	Alcohol resistant foam. Water spray, Water fog, Dry chemical powder, Carbon dioxide (CO2)

Suitable extinguishing media Unsuitable extinguishing media	Alcohol resistant foam. Water spray. Water fog. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Do not handle or store near an open flame, heat or other sources of ignition. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not re-use empty containers. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

thoroughly after handling. Observe good industrial hygiene practices.

Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Keep away from heat, sparks and open flame. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits f Components	or Air Contaminants (29 CFR 1910.1000) Type	Value
Propane (CAS 74-98-6)	PEL	1800 mg/m3
		1000 ppm
US. ACGIH Threshold Limit		N.I.
Components	Туре	Value
Butane (CAS 106-97-8)	STEL	1000 ppm
US. NIOSH: Pocket Guide to Components	Chemical Hazards Type	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm
ological limit values	No biological exposure limits noted for the ir	ngredient(s).
ppropriate engineering ontrols	Explosion-proof general and local exhaust v	entilation.
dividual protection measures, Eye/face protection	such as personal protective equipment Face shield is recommended. Wear safety g	lasses with side shields (or goggles).
Hand protection	Wear appropriate chemical resistant gloves.	
Skin protection		
Other	Wear appropriate chemical resistant clothing	3.
Respiratory protection		SH mechanical filter / organic vapor cartridge or an
Thermal hazards	Wear appropriate thermal protective clothing	g, when necessary.
eneral hygiene onsiderations		asures, such as washing after handling the material Routinely wash work clothing and protective
. Physical and chemical p	properties	
opearance	Clear. Liquid.	
Physical state	Gas.	
Form	Aerosol.	
Color	Colorless.	
dor	Mild. Solvent.	
dor threshold	Not available.	
4	Not available.	
elting point/freezing point	Not available.	
	$247 ^{\circ}\text{F}$ (175 $^{\circ}\text{C}$) estimated	
itial boiling point and boiling nge	347 °F (175 °C) estimated	
nge	-156.0 °F (-104.4 °C) Propellant estimated	
•••••••••••••••••••••••••••••••••••••••		

Upper/lower flammability or explosive limits

oppennower naminability of exp	
Flammability limit - lower (%)	1 % estimated
Flammability limit - upper (%)	7 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	60 - 70 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	658 °F (347.78 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Specific gravity	0.785 - 0.795 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use. Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

	Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. Smallest quantities reaching the lungs through swallowing or subsequent vomiting may result in lung edema or pneumonia.
	Inhalation	Not available.
	Skin contact	No adverse effects due to skin contact are expected.
	Eye contact	Direct contact with eyes may cause temporary irritation.
Symptoms related to the physical, chemical and toxicological characteristics		Exposure may cause temporary irritation, redness, or discomfort. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death. Aspiration may cause pulmonary edema and pneumonitis.
	Information on toxicological eff	fects
	Acuto toxicity	May be fatal if swallowed and enters airways. Expected to be a low bazard for usual industrial or

h

Acute toxicity

May be fatal if swallowed and enters airways. Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Components	Species	Test Results
Butane (CAS 106-97-8)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l

Components	Species	S	Test Results
Propane (CAS 74-98-6)			
Acute			
Inhalation			
LC50	Mouse		1237 mg/l, 120 Minutes
			52 %, 120 Minutes
	Rat		1355 mg/l
			658 mg/l/4h
* Estimates for product may	be based on a	additional component data	not shown.
Skin corrosion/irritation		d skin contact may cause te	
Serious eye damage/eye irritation	Direct con	tact with eyes may cause	temporary irritation.
Respiratory or skin sensitization	on		
Respiratory sensitization	Not a resp	piratory sensitizer.	
Skin sensitization	This produ	uct is not expected to caus	e skin sensitization.
Germ cell mutagenicity		vailable to indicate product c or genotoxic.	or any components present at greater than 0.1% are
Carcinogenicity	This produ	uct is not considered to be	a carcinogen by IARC, ACGIH, NTP, or OSHA.
OSHA Specifically Regulat	ted Substanc	ces (29 CFR 1910.1001-10	50)
Not listed.			
Reproductive toxicity	This produ	uct is not expected to caus	e reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classi	fied.	
Specific target organ toxicity - repeated exposure	Not classi	fied.	
Aspiration hazard	May be fa	tal if swallowed and enters	airways.
Aspiration hazard 12. Ecological information		tal if swallowed and enters	airways.
-	on Contains a		airways. risk of hazardous effects to the environment. Harmful to
12. Ecological informatio	on Contains a	a substance which causes	
12. Ecological information Ecotoxicity	on Contains a aquatic life	a substance which causes e with long lasting effects. Species	risk of hazardous effects to the environment. Harmful to
12. Ecological information Ecotoxicity Components	on Contains a aquatic life	a substance which causes e with long lasting effects. Species	risk of hazardous effects to the environment. Harmful to
12. Ecological information Ecotoxicity Components Odorless Mineral Spirits (CA	on Contains a aquatic life	a substance which causes e with long lasting effects. Species	risk of hazardous effects to the environment. Harmful to
12. Ecological information Ecotoxicity Components Odorless Mineral Spirits (CA Aquatic	Contains a aquatic life AS 64741-65-7 IC50	a substance which causes e with long lasting effects. Species 7) Algae	risk of hazardous effects to the environment. Harmful to Test Results 30000 mg/L, 72 Hours
12. Ecological information Ecotoxicity Components Odorless Mineral Spirits (CA Aquatic Algae * Estimates for product may	Contains a aquatic life AS 64741-65-7 IC50 be based on a	a substance which causes e with long lasting effects. Species 7) Algae	risk of hazardous effects to the environment. Harmful to Test Results 30000 mg/L, 72 Hours not shown.
12. Ecological information Ecotoxicity Components Odorless Mineral Spirits (CA Aquatic Algae	Contains a aquatic life AS 64741-65-7 IC50 be based on a	a substance which causes e with long lasting effects. Species 7) Algae additional component data	risk of hazardous effects to the environment. Harmful to Test Results 30000 mg/L, 72 Hours not shown.
12. Ecological information Ecotoxicity <u>Components</u> Odorless Mineral Spirits (CA Aquatic Algae * Estimates for product may Persistence and degradability	Contains a aquatic life AS 64741-65-7 IC50 be based on a No data is No data a	a substance which causes e with long lasting effects. Species 7) Algae additional component data s available on the degradat vailable.	risk of hazardous effects to the environment. Harmful to Test Results 30000 mg/L, 72 Hours not shown.
12. Ecological information Ecotoxicity Components Odorless Mineral Spirits (CA Aquatic Algae * Estimates for product may Persistence and degradability Bioaccumulative potential Partition coefficient n-octat Butane	Contains a aquatic life AS 64741-65-7 IC50 be based on a No data is No data a	a substance which causes e with long lasting effects. Species 7) Algae additional component data s available on the degradat vailable. log Kow) 2.89	risk of hazardous effects to the environment. Harmful to Test Results 30000 mg/L, 72 Hours not shown.
12. Ecological information Ecotoxicity Components Odorless Mineral Spirits (CA Aquatic Algae * Estimates for product may Persistence and degradability Bioaccumulative potential Partition coefficient n-octa Butane Propane	Contains a aquatic life AS 64741-65-7 IC50 be based on a No data is No data a anol / water (I	a substance which causes e with long lasting effects. Species 7) Algae additional component data s available on the degradat vailable. log Kow) 2.89 2.36	risk of hazardous effects to the environment. Harmful to Test Results 30000 mg/L, 72 Hours not shown.
12. Ecological information Ecotoxicity Components Odorless Mineral Spirits (CA Aquatic Algae * Estimates for product may Persistence and degradability Bioaccumulative potential Partition coefficient n-octa Butane Propane Mobility in soil	Contains a aquatic life AS 64741-65-7 IC50 be based on a No data is No data a anol / water (I	a substance which causes e with long lasting effects. Species 7) Algae additional component data s available on the degradat vailable. log Kow) 2.89 2.36 vailable.	risk of hazardous effects to the environment. Harmful to Test Results 30000 mg/L, 72 Hours not shown. bility of this product.
12. Ecological information Ecotoxicity Components Odorless Mineral Spirits (CA Aquatic Algae * Estimates for product may Persistence and degradability Bioaccumulative potential Partition coefficient n-octa Butane Propane Mobility in soil	Contains a aquatic life AS 64741-65-7 IC50 be based on a No data is No data a anol / water (I No data a anol / water (I	a substance which causes e with long lasting effects. Species 7) Algae additional component data s available on the degradat vailable. log Kow) 2.89 2.36 vailable. adverse environmental effe	risk of hazardous effects to the environment. Harmful to Test Results 30000 mg/L, 72 Hours not shown.
12. Ecological information Ecotoxicity Components Odorless Mineral Spirits (CA Aquatic Algae * Estimates for product may Persistence and degradability Bioaccumulative potential Partition coefficient n-octa Butane Propane	Contains a aquatic life AS 64741-65-7 IC50 be based on a No data is No data av anol / water (I No data av potential, o	a substance which causes e with long lasting effects. Species 7) Algae additional component data s available on the degradat vailable. log Kow) 2.89 2.36 vailable. adverse environmental effe	risk of hazardous effects to the environment. Harmful to Test Results 30000 mg/L, 72 Hours not shown. bility of this product. cts (e.g. ozone depletion, photochemical ozone creation
12. Ecological information Ecotoxicity Components Odorless Mineral Spirits (CA Aquatic Algae * Estimates for product may Persistence and degradability Bioaccumulative potential Partition coefficient n-octa Butane Propane Mobility in soil Other adverse effects	Contains a aquatic life AS 64741-65-7 IC50 be based on a No data is No data a anol / water (I No data a nol / water (I No data a nol / water a potential, o	a substance which causes e with long lasting effects. Species 7) Algae additional component data s available on the degradat vailable. log Kow) 2.89 2.36 vailable. adverse environmental effe endocrine disruption, globa	risk of hazardous effects to the environment. Harmful to Test Results 30000 mg/L, 72 Hours not shown. bility of this product. cts (e.g. ozone depletion, photochemical ozone creation al warming potential) are expected from this component. aled containers at licensed waste disposal site. Contents binerate or crush. Dispose of contents/container in accordance
12. Ecological information Ecotoxicity Components Odorless Mineral Spirits (CA Aquatic Algae * Estimates for product may Persistence and degradability Bioaccumulative potential Partition coefficient n-octa Butane Propane Mobility in soil Other adverse effects 13. Disposal consideration	Contains a aquatic life AS 64741-65-7 IC50 be based on a No data is No data as nol / water (I No data a nol / water (I No other a potential, o Cons Collect an under pres with local/	a substance which causes e with long lasting effects. Species 7) Algae additional component data a available on the degradat vailable. log Kow) 2.89 2.36 vailable. adverse environmental effe endocrine disruption, globa	risk of hazardous effects to the environment. Harmful to Test Results 30000 mg/L, 72 Hours not shown. bility of this product. tets (e.g. ozone depletion, photochemical ozone creation al warming potential) are expected from this component. eled containers at licensed waste disposal site. Contents binerate or crush. Dispose of contents/container in accordance nal regulations.

Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

ΙΑΤΑ

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo	Allowed.
aircraft	
Cargo aircraft only	Allowed.
Packaging Exceptions	LTD QTY
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to	Not applicable.
Annex II of MARPOL 73/78 and	
the IBC Code	



15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

No

Hazard categories

Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting) Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated. Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Safe Drinking Water Act Not regulated. (SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. Rhode Island RTK

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date Revision date	07-09-2014 06-10-2015
Version #	
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision Information	Product and Company Identification: Alternate Trade Names