# **SAFETY DATA SHEET**


### 1. Identification

Product number	AEZ172
Product identifier	E Z Cut
Revision date	09-23-2016
Company information	NEXGEN Pro-Line Industrial Products PO Box 401 Dixon, CA 95620
Company phone	General Assistance 1-800-263-9436
Emergency telephone US	1-800-424-9300
Version #	03
Supersedes date	12-28-2015
Recommended use	Lubricant
Recommended restrictions	None known.

### 2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
OSHA defined hazards	Not classified.	

Label elements



classified (HNOC)

**Supplemental information** None.

### 3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	40 - 60
Butane		106-97-8	10 - 20

		SDS US
Revision date: 09-23-2016	Issue date: 06-18-2015	1 / 9

Chemical name	Common name and synonyms CAS number		%
Propane		74-98-6	2.5 - 10
Other components below r	reportable levels		20 - 40

Other components below reportable levels

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

# 4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

# 5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

**Environmental precautions** Avoid discharge into drains, water courses or onto the ground.

Revision date: 09-23-2016 Issue date: 06-18-2015

SDS US 2/9

# 7. Handling and storage

Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage,	Level 2 Aerosol.
including any incompatibilities	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

#### **Occupational exposure limits**

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре		Value		
Acetone (CAS 67-64-1)	PEL		24	00 mg/m3	
			10	00 ppm	
Propane (CAS 74-98-6)	PEL		18	00 mg/m3	
			10	00 ppm	
US. ACGIH Threshold Li	mit Values				
Components	Туре		Va	lue	
Acetone (CAS 67-64-1)	STEL		50	0 ppm	
	TWA		25	0 ppm	
Butane (CAS 106-97-8)	STEL		10	00 ppm	
US. NIOSH: Pocket Guid	le to Chemical Hazards				
Components	Туре		Va	lue	
Acetone (CAS 67-64-1)	TWA	TWA 590 mg/m3		0 mg/m3	
			25	0 ppm	
Butane (CAS 106-97-8)	TWA		19	00 mg/m3	
			80	0 ppm	
Propane (CAS 74-98-6)	TWA		18	00 mg/m3	
		1000 ppm		00 ppm	
ogical limit values					
ACGIH Biological Expos	ure Indices				
Components	Value	Determinant	Specimen	Sampling Time	
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*	
* - For sampling details, pl	lease see the source docu	iment.			
			air changes per h	our) should be used	~~

Appropriate engineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

IIIMITIMMM			///////////////////////////////////////

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
Other	Wear suitable protective clothing.
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.

Revision date: 09-23-2016 Issue date: 06-18-2015

sds Us 3 / 9 General hygieneWhen using do not smoke. Always observe good personal hygiene measures, such as washing<br/>after handling the material and before eating, drinking, and/or smoking. Routinely wash work<br/>clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

	•
Appearance	
Physical state	Gas.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	90.85 °F (32.7 °C) estimated
Flash point	-156.0 °F (-104.4 °C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	2.6 % estimated
Flammability limit - upper (%)	12.8 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	238.12 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Flame extension	48 in
Oxidizing properties	Not oxidizing.
Specific gravity	0.175 estimated

# 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.

Possibility of hazardous reactions

Conditions to avoid Incompatible materials Hazardous decomposition products Hazardous polymerization does not occur.

Avoid temperatures exceeding the flash point. Contact with incompatible materials. Strong oxidizing agents. Nitrates. Fluorine. Chlorine. No hazardous decomposition products are known.

Revision date: 09-23-2016 Issue date: 06-18-2015

sds Us 4 / 9

# 11. Toxicological information

# Information on likely routes of exposure

Information on likely routes of	exposure	
Inhalation	May cause drowsiness and dizziness. harmful.	Headache. Nausea, vomiting. Prolonged inhalation may be
Skin contact	No adverse effects due to skin contact	are expected.
Eye contact	Causes serious eye irritation.	
Ingestion	Expected to be a low ingestion hazard.	
Symptoms related to the physical, chemical and toxicological characteristics	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.	
Information on toxicological e	ffects	
Acute toxicity	Narcotic effects.	
Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
Dermal		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
Inhalation		
LC50	Rat	55700 ppm, 3 Hours
		132 mg/l, 3 Hours
		50.1 mg/l
Oral		
LD50	Rat	5800 mg/kg
		2.2 ml/kg
Butane (CAS 106-97-8)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
Propane (CAS 74-98-6)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %. 120 Minutes

Rat

52 %, 120 Minutes 1355 mg/l 658 mg/l/4h

* Estimates for product may	y be based	on additional	component	t data not sh	iown.
-----------------------------	------------	---------------	-----------	---------------	-------

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitizatio	n	
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
		SDS US
Revision date: 09-23-2016 Issue da	ate: 06-18-2015	5/9

IARC Monographs. Overall Evaluation of Carcinogenicity			
Not listed.	Not listed.		
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)			
Not regulated.			
US. National Toxicology Pro	gram (NTP) Report on Carcinogens		
Not listed.			
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.		
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not likely, due to the form of the product.		
Chronic effects	Prolonged inhalation may be harmful.		

# 12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

		<b>o</b> 1 1	00
Product		Species	Test Results
12 OZ E Z CUT LB 12	PK		
Aquatic			
Crustacea	EC50	Daphnia	22251.1855 mg/l, 48 hours estimated
Fish	LC50	Fish	1096.5597 mg/l, 96 hours estimated
Components		Species	Test Results
Acetone (CAS 67-64-1	)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

#### **Bioaccumulative potential**

Partition coefficient n-o	ctanol / water (log Kow)	
Acetone	-0.24	
Butane	2.89	
Propane	2.36	
Mobility in soil No data available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creat potential, endocrine disruption, global warming potential) are expected from this compone	

### 13. Disposal considerations

		Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
	Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the was		

	disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

Revision date: 09-23-2016 Issue date: 06-18-2015

sds us 6 / 9

# 14. Transport information

$\sim$	т.
 IJ	

DOT	
UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None
IATA	None
UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	0.4
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo	Allowed with restrictions.
aircraft	
Cargo aircraft only	Allowed with restrictions.
Packaging Exceptions	LTD QTY
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to	Not applicable.
Annex II of MARPOL 73/78 and	
the IBC Code	
DOT	





Revision date: 09-23-2016 Issue date: 06-18-2015

sds us 7 / 9 IATA; IMDG



# 15. Regulatory information

ro. Regulatory information		
US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.	
TSCA Section 12(b) Export	Notification (40 CFR 707, Subpt. D)	
Not regulated.		
CERCLA Hazardous Substa	Ince List (40 CFR 302.4)	
Acetone (CAS 67-64-1)	Listed.	
SARA 304 Emergency relea		
Not regulated.		
0	ed Substances (29 CFR 1910.1001-1050)	
Not regulated.		
6		
-	eauthorization Act of 1986 (SARA)	
Hazard categories	Immediate Hazard - Yes	
	Delayed Hazard - No Fire Hazard - Yes	
	Pressure Hazard - No	
	Reactivity Hazard - No	
SARA 302 Extremely hazard	dous substance	
Not listed.		
SARA 311/312 Hazardous chemical	No	
SARA 313 (TRI reporting) Not regulated.		
Other federal regulations		
Clean Air Act (CAA) Sectior	n 112 Hazardous Air Pollutants (HAPs) List	
Not regulated.		
0	n 112(r) Accidental Release Prevention (40 CFR 68.130)	
Butane (CAS 106-97-8)		
Propane (CAS 74-98-6)		
Safe Drinking Water Act (SDWA)	Not regulated.	
Drug Enforcement Adm Chemical Code Number	inistration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and r	
Acetone (CAS 67-64	-1) 6532	
•	ninistration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))	
Acetone (CAS 67-64		

# DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1)

6532

## US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (CAS 67-64-1) Butane (CAS 106-97-8)

Revision date: 09-23-2016 Issue date: 06-18-2015

#### **US. Massachusetts RTK - Substance List**

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Propane (CAS 74-98-6)

#### US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Propane (CAS 74-98-6)

#### US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Propane (CAS 74-98-6)

#### US. Rhode Island RTK

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Propane (CAS 74-98-6)

#### US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

#### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,4-Dioxane (CAS 123-91-1)	Listed: January 1, 1988			
Ethylene Oxide (CAS 75-21-8)	Listed: July 1, 1987			
Propylene Oxide (CAS 75-56-9)	Listed: October 1, 1988			
US - California Proposition 65 - CRT: Listed date/Developmental toxin				
Ethylene Oxide (CAS 75-21-8) US - California Proposition 65 - CRT: Listed of	Listed: August 7, 2009 date/Female reproductive toxin			
Ethylene Oxide (CAS 75-21-8)	Listed: February 27, 1987			
US - California Proposition 65 - CRT: Listed date/Male reproductive toxin				
Ethylene Oxide (CAS 75-21-8)	Listed: August 7, 2009			

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Listed Otatas 0 Duanta Dias		

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

Issue date	06-18-2015		
Revision date	09-23-2016		
Version #	03		
Disclaimer	We cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.		

		SDS US
Revision date: 09-23-2016	Issue date: 06-18-2015	9 / 9