



## **Fast Steel**

**DESCRIPTION:** FAST STEEL is a steel reinforced epoxy putty. FAST STEEL is a hand kneadable, non-rusting epoxy for repairs or rebuilds of anything made of metal. FAST STEEL dries in minutes, with a full cure in only 1 hour. FAST STEEL is an industrial strength product, which bonds tenaciously to most metal surfaces. After final cure, FAST STEEL can be drilled, tapped, machined, ground or filed. FAST STEEL will not shrink or pull away, and contains no harsh solvents. FAST STEEL is quick, easy to use, economical and fool proof, with no liquid mixing or measuring required.

**ADVANTAGES:** 1) Base epoxy and curing agent wrapped in one tube. 2) Cures in only 1 hour. 3) Cut off only amount desired, making product very economical to use. 4) Soft putty texture makes for easy kneading. 5) No pre mixing or measuring of liquids required. 6) Non fuming formulation allows for use in any area. 7) Bonds to virtually all metal surfaces with little preparation required. 8) Chemically resistant to hydrocarbons, halocarbons, ketones, alcohols, esters, aqueous salt solutions, diluted acid and bases.

**AREAS OF USE:** Rebuild small engine parts, seal leaks, fill cracks, form nuts and bolts, repair stripped threads, anchor machines, repair metal tools, repair equipment, ducts, pipes, tanks, water pans, rain gutters and much more.



### **SPECIFICATIONS:**

<b>Classification</b>	<b>Epoxy putty tube</b>
<b>Color</b>	<b>Battleship gray</b>
<b>Working life (minutes)</b>	<b>3 - 5</b>
<b>Cure time (minutes)</b>	<b>60</b>
<b>Shrinkage</b>	<b>&gt;1%</b>
<b>Electrical resistance (megohms)</b>	<b>30,000</b>
<b>Dielectric strength (volts/mil)</b>	<b>300</b>
<b>Shelf life (minimum)</b>	<b>12 months @ 75° F</b>

**Certified 100% Women-Owned Small Business**

**Dedicated to Integrity • Reliability • Quality Products • Friendly Service**

**Our Products are Made in the USA and we Proudly Support Veteran Endowments**