

Industrial Products



Quick Wood

DESCRIPTION: QUICK WOOD is a hand mixable epoxy putty specially formulated to repair and rebuild wood quickly and easily. QUICK WOOD has a curing agent encapsulated in a contrasting color base material. When mixed together, the materials combine to form a polymer compound that cures to the same density and light brown color of most woods. QUICK WOOD becomes an integral part of the item being prepared. QUICK WOOD may be used for exterior or interior applications, contains no solvents, and will not shrink, crack, rot or pull away. After final cure, QUICK WOOD can be drilled, tapped, machined, sanded, filed or stained.

ADVANTAGES: 1) Easy to use, simply twist or cut off required amount of product, knead with fingers to a uniform color and apply to surface to be repaired. 2) QUICK WOOD has a 15 to 25 minute work life and hardens in 60 minutes to form a tenacious bond. 3) QUICK WOOD fully cures in 24 hours.

AREAS OF USE: Repairs to any wood surface such as tables, dry rot, knot holes, window and door frames, screw holes and much more.



SPECIFICATIONS:

Classification Epo	xy putty
Color Ligi	ht brown
Working life (minutes)	15 - 25
Shrinkage	<1%
Cure time (hours)	24
Dielectric strength (volts/mil)	300
Electrical resistance (megohms)	30.000

Certified 100% Women-Owned Small Business Dedicated to Integrity • Reliabilty • Quality Products • Friendly Service Our Products are Made in the USA and we Proudly Support Veteran Endowments