



Industrial Products



Quik Aluminum

DESCRIPTION: QUIK ALUMINUM is an aluminum reinforced epoxy putty. QUIK ALUMINUM is a hand kneadable, non rusting epoxy that hardens to an aluminum-like substance. QUIK ALUMINUM dries in minutes, with a full cure in only 1 hour. QUIK ALUMINUM is a specialty epoxy which bonds tenaciously to most metals. After final cure, QUIK ALUMINUM can be drilled, tapped, machined, ground or filed. QUIK ALUMINUM will not shrink or pull away, and contains no harsh solvents. QUIK ALUMINUM is quick, easy to use, economical and fool proof, with no liquid mixing or measuring needed. Shear tensile strength on aluminum (1"x 1"x 1/16") lbs 400 - 600.

ADVANTAGES: 1) Base epoxy and curing agent wrapped in one tube. 2) Cures in only 1 hour. 3) Cut off only amount desired, making product very economical to use. 4) Soft putty texture makes for easy kneading. 5) No pre mixing or measuring of liquids required. 6) Non fuming formulation allows for use in any area. 7) Bonds to most metals with little preparation required. 8) Chemically resistant to hydrocarbons, ketones, alcohols, esters, halocarbons, aqueous salt solutions and dilute acids and bases.

AREAS OF USE: Repairs to - gutters, storm doors, windows, shower frames, aluminum siding, air conditioning units, machine parts, wheels and much more.



SPECIFICATIONS:

Classification	Epoxy putty tube
Color	Gray
Working life (minutes)	5 - 7
Cure time (minutes)	60
Shrinkage	<1%
Electrical resistance (megohms)	30,000
Dielectric strength (volts/mil)	300

Certified 100% Women-Owned Small Business

Dedicated to Integrity • Reliability • Quality Products • Friendly Service

Our Products are Made in the USA and we Proudly Support Veteran Endowments