Safety Data Sheet

Ultra Pen Cherry

SECTION I - IDENTIFICATION

PRODUCT NAME: Ultra Pen Cherry

PRODUCT CODE: ACH452

PRODUCT USE: Penetrating Oil/Lubricant

COMPANY NAME: Pro-Line Industrial Products, Inc **COMPANY ADDRESS:** PO Box 401 Dixon, CA 95620

COMPANY PHONE: 800-263-9436 **EMERGENCY PHONE:** 800-424-9300

SECTION II – HAZARDS IDENTIFICATION

CLASSIFICATION: Dissolved Gas

Eye Irritant: Category 2A Aspiration Hazard: Category 1 Skin Irritant: Category 2

HAZARD STATEMENT(S): DANGER: Contains gas under pressure; May explode if heated. Causes skin and serious eye irritation.

May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: 0%

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Wash hands thoroughly after handling. If in eyes: rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical attention. Wear protective gloves and eye protection. If swallowed: immediately call a poison center or a doctor. Do NOT induce vomiting. Store locked up. Dispose of contents/container in accordance with local/regional/national guidelines. IF ON SKIN: Wash with soap and water If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse

SYMBOL:







HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

| HAZARDOUS INGREDIENT | CAS NUMBER | PERCENT |
|---|------------|---------|
| Distillates (petroleum), hydrotreated light | 64742-47-8 | 30-60% |
| Distillates (Petroleum), Solvent Dewaxed Heady Paraffinic | 64742-65-0 | 15-20% |
| Carbon Dioxide | 124-38-9 | 1-5% |
| Trans, 1,2-Dichloroethylene | 156-60-5 | 15-20% |

SECTION IV - FIRST AID MEASURES

EYES: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

INGESTION: If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting.

INHALATION: Move to fresh air. If breathing is difficult, administer oxygen. If not breathing administer artificial respiration. Seek immediate medical attention.

SKIN: If on skin: Wash with plenty of water. If skin irritation occurs: get medical attention.

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision

Skin: defatting and dermatitis

CHRONIC HEALTH HAZARDS: Long-term exposure may cause dermatitis

NOTE TO PHYSICIAN: If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

SECTION V - FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, foam, or Carbon Dioxide (CO₂).

UNSUITABLE EXTINGUISHING MEDIA: Water spray/stream.

SPECIAL FIRE FIGHTING PROCEDURES: Wear full protective clothing and NIOSH approved SCBA with full facepiece operated in positive pressure or pressure demand. Use water mist to keep material cool in fire situations.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Absorb spill with non-combustible material such as vermiculite, sand or earth.

WASTE DISPOSAL: Do not puncture container, wrap container and place in trash collection.

RCRA STATUS: Waste likely considered hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII - HANDLING AND STORAGE

HANDLING AND STORAGE: Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Pressurized container: Do not pierce or burn, even after use. Store locked up.

OTHER PRECAUTIONS: Vapors may collect in low lying areas. Keep out of the reach of children. Do not ingest. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes.

INCOMPATIBILITY: Strong oxidizing agents, strong reducing agents, acids.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

| HAZARDOUS INGREDIENT | OSHA PEL | ACGIH TLV |
|---|----------|-----------|
| Distillates (petroleum), hydrotreated light | N/A | 200 mg/m3 |
| Distillates (Petroleum), Solvent Dewaxed | 5 mg/m3 | 10 mg/m3 |
| Heady Paraffinic | | |
| Carbon Dioxide | 5000 ppm | 5000 ppm |
| Trans, 1,2-Dichloroethylene | 200 ppm | 200 ppm |

ENGINEERING CONTROLS / VENTILATION: Use only in well ventilated areas. Local ventilation/exhaust preferred. **RESPIRATORY PROTECTION:** Wear NIOSH/MSHA approved respiratory protection if exposure limits are exceeded.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses and chemical resistant gloves

ADDITIONAL MEASURES: Wash hands thoroughly after handling.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Amber Tinted Spray

ODOR: Cherry Scent

ODOR THRESHOLD: N/D BOILING POINT: N/D FREEZING POINT: N/D

FLAMMABILITY: Not considered a flammable aerosol or an extremely flammable aerosol by OSHA (29CFR 1910.1200)

FLASH POINT: $> 200^{\circ}F$

AUTOIGNITION TEMPERATURE: N/D LOWER FLAMMABILITY LIMIT: N/D UPPER FLAMMABILITY LIMIT: N/D VAPOR PRESSURE (mm Hg): 85 PSI

VAPOR DENSITY (AIR=1): $> 1 @ 77^{\circ}F (25^{\circ}C)$

EVAPORATION RATE: Slow

SPECIFIC GRAVITY (H2O=1): 0.868

Safety Data Sheet

pH: N/A

SOLUBILITY IN WATER: Non-soluble

PARTITION COEFFICIENT: n-OCTANOL/WATER (Kow): N/D

VOLATILE ORGANIC COMPOUNDS (VOC): 20.2%

DECOMPOSITION TEMPERATURE: N/D

VISCOSITY: N/D

SECTION X – STABILITY AND REACTIVITY DATA

REACTIVITY: If exposed to strong oxidizers, presents explosion hazard.

CHEMICAL STABILITY: Stable

CONDITIONS TO AVOID: Excessive heat.

INCOMPATIBILITY: Strong oxidizing agents, strong reducing agents, acids. HAZARDOUS DECOMPOSITION OR BY-PRODUCT: Oxides of carbon

POSSIBLE HAZARDOUS REACTIONS: None Known

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Distillates (petroleum), hydrotreated light: (64742-47-8) LD50 Dermal, Rabbit: > 2000

mg/kg, LD50 ral, Rat, >5000 mg/kg

ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin

EYES: May cause irritation, redness.

INGESTION: May cause gastrointestinal irritation, nausea, diarrhea, vomiting, aspiration hazard.

INHALATION: Causes mild irritation to the respiratory tract.

SKIN: May cause irritation, localized defatting.

MEDICAL CONDITION AGGRAVATED: None known

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision

Skin: defatting and dermatitis

CHRONIC HEALTH HAZARDS: Long-term exposure may cause dermatitis

CARCINOGENICITY: OSHA: No ACGIH: No NTP: No IARC: No OTHER: N/A

SECTION XII – ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Distillates (petroleum), hydrotreated light (64742-47-8) Not expected to be harmful or

demonstrate chronic toxicity toward aquatic organisms. Expected to be readily biodegradable. Do not contaminate water when disposing of equipment washwaters.

BIODEGRADABILITY: Component or components of this product are not biodegradable.

BIOACCUMULATION: This product is not expected to bioaccumulate.

SOIL MOBILITY: This product is mobile in soil. OTHER ECOLOGICAL HAZARDS: None Known

SECTION XIII - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Do not puncture container, wrap container and place in trash collection.

RCRA STATUS: Waste likely considered hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.2 UN/NA NUMBER: UN 1950 PACKAGING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.2 UN/NA NUMBER: UN 1950

Safety Data Sheet

SHIPPING BY WATER: VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.2 UN/NA NUMBER: UN 1950

ENVIRONMENTAL HAZARDS WATER: N/A

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All Chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): None

SARA 311/312 HAZARD CATEGORIES: None SARA 313 REPORTABLE INGREDIENTS: None STATE REGULATIONS: California Proposition 65: None

INTERNATIONAL REGULATIONS: All components are listed or exempted.

NFPA HEALTH: 2
NFPA FLAMMABILITY: 1
NFPA REACTIVITY: 0
HMIS HEALTH: 2
HMIS FLAMMABILITY: 1
HMIS REACTIVITY: 0

NFPA OTHER: None HMIS PROTECTION: B

SECTION XVI - ADDTIONAL INFORMATION

DATE PREPARED: 07/07/2016 **REVISION DATE:** 07/07/2016

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.