# **ASAP Copper**

## SAFETY DATA SHEET

#### **SECTION 1: IDENTIFICATION**

Manufacturer: Pro-Line Industrial Nexgen Brand

723 W. University Ave

#110-428

Georgetown, TX 78626

800-263-9436

Emergency Phone Number: Chemtrec (800) 424-9300

Product Identification: BAS206 Product Use: Anti-Seize Compound Restriction on Use: None known

SDS Date of Preparation: January 10,2022

#### **SECTION 2: HAZARDS IDENTIFICATION**

#### GHS Classification (Hazcom 2012):

Not Hazardous in accordance with OSHA Haz. Com. Standard 29 CFR 1910.1200.

#### **Label Elements:**



Signal Word: Warning

## **Hazard Phrases:**

Gases under pressure.

Pressurized container; Do not pierce or burn even after use.

## **Precautionary Phrases:**

Keep out of reach of children.

Pressurized container; Do not pierce or burn, even after use.

Wash with soap and water thoroughly after handling.

#### Response:

IF ON SKIN: Wash with soap and water

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF IN EYES: Remove contact lenses if present and easy to do, continue rinsing.

**Storage:** Store at temperatures not exceeding 122°F (50°C)

**Disposal:** Dispose of in accordance with local, state, and federal regulations.

Other Hazards: None

#### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS#	%
Synthetic Base Oil	NJTSRN#1210-01	50-80
Copper	7440-50-8	20-30
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	5-15
Rust inhibitor	Mixture	1-5

The specific identity and/or exact percentage of composition has been withheld as a trade secret.

#### **SECTION 4: FIRST AID MEASURES**

**Eye:** Flush eyes with water, holding the eyelids apart. Get medical attention if irritation develops or persists.

Skin: Wash thoroughly with plenty of water. Get medical attention if irritation persists.

**Inhalation:** Remove to fresh air and keep comfortable for breathing. If irritation occurs, get medical attention.

**Ingestion:** If large amounts ingested, seek medical attention.

Most Important symptoms and effects, both acute and delayed: None known.

**Indication of any immediate medical attention and special treatment needed:** Immediate medical attention generally not required.

## **SECTION 5: FIRE-FIGHTING MEASURES**

Suitable and Unsuitable Extinguishing Media: Use water spray or fog, foam, carbon dioxide or dry chemical.

**Special Hazards Arising from the Chemical:** This compound will not burn unless it is pre-heated. Water fog may be used to cool the containers but do not spray directly into large containers of burning liquids as frothing may occur. Dense smoke and noxious or toxic fumes may be generated in a fire. Thermal decomposition may yield oxides of carbon.

**Special Equipment and Precautions for Fire-Fighters:** Wear NIOSH approved positive pressure, self-contained breathing apparatus and full protective clothing. Cool fire exposed containers with water.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

**Personal Precautions, Protective Equipment and Emergency Procedures:** Wear appropriate personal protective equipment. Use caution: slip hazard.

Environmental Hazards: Report spills and releases as required to appropriate authorities.

**Methods and Material for Containment and Cleaning Up:** Collect spill with an inert absorbent material and place into a suitable container for disposal. Clean area thoroughly.

#### **SECTION 7: HANDLING AND STORAGE**

**Precautions for Safe Handling:** Avoid contact with eyes. Avoid prolonged skin contact Do not transfer to unlabeled containers.

**Conditions for Safe Storage, Including any Incompatibilities:** Store away from extreme heat and open flames. Store away from oxidizers.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

Chemical Name	Exposure Limits
Synthetic Base Oil	5 mg/m3 TWA ACGIH TLV (inhalable) 5 mg/m3 TWA OSHA PEL
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m3 TWA ACGIH TLV (inhalable) 5 mg/m3 TWA OSHA PEL
Copper	1 mg/m3 TWA ACGIH TLV 1 mg/m3 TWA OSHA PEL
Rust inhibitor	None Established

**Appropriate Engineering Controls:** Use with adequate general or local exhaust ventilation to maintain exposure levels below the exposure limits. If the product is used at high temperatures, local exhaust ventilation may be required.

#### **Individual Protection Measures:**

**Respiratory Protection:** In operations where the occupational exposure limits are exceeded or if use at elevated temperature where smoke is produced, a NIOSH approved respirator with organic vapor/particulate cartridges or supplied air respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.

**Skin Protection:** Impervious gloves such as rubber or nitrile recommended where needed to avoid prolonged skin contact.

Eye Protection: Safety glasses or goggles recommended where needed to avoid eye contact.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Copper colored paste	Vapor Density (air = 1): Not available	
Odor: Slight odor	Specific Gravity: 1.2	
Odor Threshold: Not established	Water Solubility: Not soluble	
pH: Not available	Octanol/Water Partition Coefficient: Not	
	available	
Melting Point/Freezing Point: Not available	Autoignition Temperature: Not available	
Boiling Point: >500°F	<b>Decomposition Temperature:</b> Not available	
Flash Point: >350°F	Viscosity: Not available	
Evaporation Rate: Not available	Explosion Properties: None	
Flammable Limits:	Oxidizing Properties: Not oxidizing	
LEL: Not established		
UEL: Not established		
Vapor Pressure: Not established	Aerosol Fire Protection Level: Not applicable	
VOC Content: <0.5%	Flammability (solid, gas): Not available	

#### **SECTION 10: STABILITY AND REACTIVITY**

**Reactivity:** Not reactive under normal conditions of use.

Chemical Stability: Stable under normal storage and handling conditions.

Possibility of Hazardous Reactions: None known

Conditions to Avoid: Use with strong oxidizing chemicals such as concentrated acids.

Incompatible Materials: Avoid strong oxidizing agents and acids.

Hazardous Decomposition Products: Thermal decomposition products may yield oxides of carbon.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

#### **Potential Health Effects:**

Eye: May cause mild irritation.

**Skin:** Prolonged contact may cause irritation and drying of the skin.

**Inhalation:** No adverse effects expected at ambient temperatures. Inhalation of vapors and fumes from thermal decomposition may cause respiratory irritation and metal fume fever with symptoms of fever and chills.

Ingestion: Swallowing may cause gastrointestinal irritation, nausea, vomiting, diarrhea.

Chronic Hazards: Prolonged inhalation of thermal decomposition products may result in lung damage.

**Carcinogen Status:** None of the components of this product are listed as carcinogens by IARC, NTP or OSHA.

#### **Acute Toxicity Values:**

**Copper:** Oral rat LD50 > 2500 mg/kg, inhalation rat LC50 > 5.11 mg/L, dermal rat LD50 > 2000 mg/kg **Distillates (petroleum), hydrotreated heavy naphthenic:** Oral rat LD50 > 5000 mg/kg, inhalation rat LC50: 2.18 mg/L, dermal rabbit LD50 > 2000 mg/kg

#### **SECTION 12: ECOLOGICAL INFORMATION**

## **Ecotoxicity:**

**Copper:** Salmo gairdneri LC50: 190 ug/L/96hr. Copper is classified as toxic to aquatic organisms.

Distillates (petroleum), hydrotreated heavy naphthenic: Pimephales promelas LL50 > 100 mg/L/96hr.

Persistence and Degradability: No data available

Bioaccumulative Potential: No data available

Mobility in Soil: No data available

Other Adverse Effects: None known

## **SECTION 13: DISPOSAL CONSIDERATIONS**

Dispose in accordance with all local, regional and national regulations.

#### **SECTION 14: TRANSPORT INFORMATION**

DOT

Proper Shipping Name: aerosols

**DOT Hazard Class**: 2.2 **UN Number**: UN 1950 **Packing Group**: None

**IMDG** 

Shipping Description: Aerosols

Hazard Class: 2.2

**Identification Number: UN 1950** 

Packing Group: none

ICAO/IATA

Shipping Description: Aerosols, non-flammable

ID Number: UN 1950 Hazard Class: 2.2 Packing Group: None

## **SECTION 15: REGULATORY INFORMATION**

Safety, health, and environmental regulations specific for the product in question.

**CERCLA Hazardous Substances (Section 103)/RQ:** This product has a Reportable Quantity (RQ) of 16,667 lbs. (based on the RQ for Copper of 5,000 lbs present at 20-30%). Releases above the RQ must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA Hazard Category (311/312): Not Hazardous

**SARA 313:** This product contains the following chemicals regulated under SARA Title III, section 313: Copper, 20-30%

**EPA TSCA Inventory:** All of the components of this product are listed on the TSCA inventory.

**CALIFORNIA PROPOSITION 65:** This product is not known to contain listed chemicals.

#### **SECTION 16: OTHER INFORMATION**

Revision Summary: New format to comply with OSHA Hazcom 2012

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.