

# SAFETY DATA SHEET

## SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

**Product ID:** STAR SHINE GLASS CLEANER  
**Product Name:** STAR SHINE GLASS CLEANER  
**Revision Date:** Dec 21, 2021  
**Version:** 4.0  
**Distributor's Name:** PRO-LINE INDUSTRIAL PRODUCTS  
**Address:** 723 W UNIVERSITY AVE #110-428 - GEROGETOWN, TX 78626  
**Emergency Phone:** 1-800-535-5053  
**Information Phone Number:** (800) 263-9436  
**Fax:**  
**Product/Recommended Uses:** Glass Cleaner

**Date Printed:** 1/11/22  
**Supersedes Date:** May 6, 2021

## SECTION 2) HAZARDS IDENTIFICATION

### Classification

Gases Under Pressure - Compressed Gas  
Specific Target Organ Toxicity - Repeated Exposure - Category 2  
Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 1.3% (oral), 3.8% (dermal), 1.3% (inhalation)

### Pictograms



### Signal Word

Warning

### Hazardous Statements - Physical

H280 - Contains gas under pressure; may explode if heated.

### Hazardous Statements - Health

H373 - May cause damage to organs through prolonged or repeated exposure.

### Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P103 - Read label before use.

### Precautionary Statements - Prevention

P260 - Do not breathe mist, vapors or spray.

### Precautionary Statements - Response

P314 - Get medical advice or attention if you feel unwell.

### Precautionary Statements - Storage

P410 + P403 - Protect from sunlight. Store in a well-ventilated place.

### Precautionary Statements - Disposal

### Supplemental label elements

DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Please refer to the SDS for additional information. Keep out of reach of children. Keep upright in a cool, dry place. Do not discard empty can in trash compactor.

## SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
111-76-2	2-BUTOXYETHANOL	1% - 3%
106-97-8	BUTANE	1% - 3%
64-17-5	ETHANOL	1% - 3%
74-98-6	PROPANE	1% - 3%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

## SECTION 4) FIRST-AID MEASURES

### Inhalation

Remove to fresh air. Administer oxygen if needed. Apply artificial respiration if breathing has stopped. Get medical attention.

### Eye Contact

Wash immediately with large volumes of fresh water for at least 15 minutes. Get medical attention.

### Skin Contact

Flush with plenty of water. Wash with soap and water. Get medical attention if irritation persists.

### Ingestion

Ingestion is not a likely route of exposure. Get medical attention if you feel unwell.

## SECTION 5) FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Use extinguishing agent suitable for the surrounding fire.

### Unsuitable Extinguishing Media

Water may be ineffective but can be used to cool containers exposed to heat or flame.

### Specific Hazards in Case of Fire

Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharge contents. Liquid content of container will not support combustion. Bursting aerosol containers may be propelled from a fire at high speed. Hazardous decomposition products include carbon dioxide, carbon monoxide, and other toxic fumes.

### Fire-Fighting Procedures

Water may be used to cool containers to prevent pressure build-up and explosion when exposed to extreme heat.

### Special Protective Actions

Wear goggles and use a self-contained breathing apparatus. If water is used, fog nozzles are preferred.

## SECTION 6) ACCIDENTAL RELEASE MEASURES

### Emergency Procedure

Avoid breathing vapors. Ventilate area. Remove all sources of ignition.

### Recommended Equipment

Clean up with an absorbent material and place in closed containers for disposal.

### Personal Precautions

Avoid breathing vapors. Ventilate area. Wear safety glasses and gloves.

### Environmental Precautions

Stop spill/release if it can be done safely.

## SECTION 7) HANDLING AND STORAGE

### General

Do not puncture or incinerate (burn) cans. Do not stick pins, nails, or any other sharp objects into opening on top of can. Do not spray in eyes. Do not take internally.

### Ventilation Requirements

Use in a well-ventilated place.

### Storage Room Requirements

Store and use in a cool, dry, well-ventilated area. Do not store above 120°F. See product label for additional information.

## SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

### Eye Protection

Safety glasses with side shields should be used if indicated. Eye wash and safety showers in the workplace are recommended.

### Skin Protection

Use solvent-resistant protective gloves for prolonged or repeated contact.

### Respiratory Protection

In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapor. In confined areas, use an approved air line respirator or hood. A self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

### Appropriate Engineering Controls

Ventilation should be sufficient to prevent inhalation of any vapors.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)
BUTANE								800
ETHANOL	1000	1900			1			1000
2-BUTOXY-ETHANOL	50	240			1		1	5
PROPANE	1000	1800			1			1000

Chemical Name	NIOSH TWA (mg/m3)	NIOSH STEL (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinogen	ACGIH TWA (ppm)	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)
BUTANE	1900						1000 (EX)	
ETHANOL	1900						1000	
2-BUTOXY-ETHANOL	24				20			
PROPANE	1800						Simple asphyxiant (D), explosion hazard (EX)	

## SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

### Physical and Chemical Properties

Density	7.96 lb/gal
Density VOC	0.80 lb/gal
% VOC	10.0 %

Appearance	N.A.
Odor Threshold	N.A.
Odor Description	N.A.
pH	10.1
Water Solubility	N.A.
Flammability	N.A.
Flash Point Symbol	N.A.
Flash Point	Closed cup: -29°C/-20.2°F [Pensky-Martens Closed Cup]
Viscosity	Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)
Lower Explosion Level	1.1%
Upper Explosion Level	19%
Melting Point	N.A.
Vapor Pressure	101.3 kPa (760 mm Hg)
Freezing Point	N.A.
Low Boiling Point High	N.A.
Boiling Point	N.A.
Decomposition Pt	N.A.
Auto Ignition Temp	N.A.
Evaporation Rate	89 (butyl acetate = 1)

## SECTION 10) STABILITY AND REACTIVITY

### Stability

The product is stable under normal storage conditions.

### Conditions to Avoid

High temperatures.

### Incompatible Materials

None known.

### Hazardous Reactions/Polymerization

None known.

### Hazardous Decomposition Products

Hazardous decomposition products may include carbon dioxide, carbon monoxide, and other toxic fumes.

## SECTION 11) TOXICOLOGICAL INFORMATION

### Skin Corrosion/Irritation

Based on available data, the classification criteria are not met.

### Serious Eye Damage/Irritation

Based on available data, the classification criteria are not met.

### Carcinogenicity

Based on available data, the classification criteria are not met.

### Germ Cell Mutagenicity

Based on available data, the classification criteria are not met.

### Reproductive Toxicity

Based on available data, the classification criteria are not met.

### Respiratory/Skin Sensitization

Based on available data, the classification criteria are not met.

### Specific Target Organ Toxicity - Single Exposure

Based on available data, the classification criteria are not met.

### Specific Target Organ Toxicity - Repeated Exposure

May cause damage to organs through prolonged or repeated exposure.

### Aspiration Hazard

Based on available data, the classification criteria are not met.

### Acute Toxicity

Based on available data, the classification criteria are not met.

### Likely Routes of Exposure

Inhalation, Skin contact, Eye contact

### Potential Health Effects - Miscellaneous

000064-17-5 ETHANOL

The following medical conditions may be aggravated by exposure: liver disease. Tests in some laboratory animals indicate this compound may have embryotoxic activity. Tests in animals demonstrate reproductive toxicity. Ingestion may cause any of the following: stupor (central nervous system depression), gastrointestinal irritation. If absorbed through the skin, may be: harmful.

0000111-76-2 2-BUTOXYETHANOL

Can be absorbed through the skin in harmful amounts. May cause injury to the kidneys, liver, blood and/or bone marrow. Repeated overexposure may result in damage to the blood. Eye contact may cause corneal injury. Has been toxic to the fetus in laboratory animals at doses that are toxic to the mother.

## SECTION 12) ECOLOGICAL INFORMATION

### Toxicity

Based on available data, the classification criteria are not met.

64-17-5 ETHANOL

S gairdneri: 13.0g/l (96hr LC50) Nauplii : 858 g/l (48hr EC50) Ceriodaphnia dubia : 9.6mg/l (10 day NOEC) Freshwater Fish 250mg/l (NOEC) Reference: REACH registration Dossier

### Classification of the substance or mixture

There is no ecological data available for this product.

### Persistence and Degradability

64-17-5 ETHANOL

Readily biodegradable. Half-life in air = 38 h

106-97-8 BUTANE

Readily biodegradable.

111-76-2 2-BUTOXYETHANOL

Readily biodegradable

### Bioaccumulative Potential

64-17-5 ETHANOL

Substance has a low potential for bioaccumulation (log Kow3)

### Mobility in Soil

No data available.

### Other Adverse Effects

No data available.

## SECTION 13) DISPOSAL CONSIDERATIONS

### Waste Disposal

Under RCRA, it is the responsibility of the user of the product, to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state, and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

## SECTION 14) TRANSPORTATION INFORMATION

	U.S. DOT Information	IMDG Information	IATA Information
<b>UN number:</b>	UN1950	UN1950	UN1950
<b>Proper shipping name:</b>	Aerosols	Aerosols	Aerosols, non-flammable
<b>Hazard class:</b>	2.2	2.2	2.2
<b>Packaging group:</b>	N.A.	N.A.	N.A.
<b>Hazardous substance (RQ):</b>	No Data Available		
<b>Marine Pollutant:</b>	No Data Available	No Data Available	
<b>Note / Special Provision:</b>	(LTD QTY)	(LTD QTY)	(LTD QTY)
<b>Toxic-Inhalation Hazard:</b>	No Data Available		

## SECTION 15) REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
111-76-2	2-BUTOXYETHANOL	1% - 3%	SARA313, CERCLA, SARA312, TSCA, OSHA
106-97-8	BUTANE	1% - 3%	SARA312, TSCA
64-17-5	ETHANOL	1% - 3%	SARA312, TSCA, OSHA
74-98-6	PROPANE	1% - 3%	SARA312, TSCA, OSHA

## SECTION 16) OTHER INFORMATION

### Glossary

\* There are points of differences between OSHA GHS and UN GHS. In 90% of the categories, they can be used interchangeably, but for the Skin Corrosion/Irritant Category and the Specific Target Organ Toxicity (Single and Repeated Exposure) Categories. In these cases, our system will say UN GHS.

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

### HMIS

Health	* 2
FLAMMABILITY	2
Physical Hazard	3
Personal Protection	B

(\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

---

## DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.