Safety Data Sheet

SECTION 1: Product and company identification

Product name : Clear Away
Use of the substance/mixture : Drain maintainer

Product code : QCA307

Company : PRO-LINE INDUSTRIAL PRODUCTS 723 W UNIVERSITY AVE. 110-428

GEORGETOWN, TX 78626 - US

T 800-263-9436

Emergency number : 800-424-9300 Chemtrec

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Acute Tox. 3 (Oral) H301 Acute Tox. 4 (Dermal) H312 Skin Corr. 1A H314

2.2. Label elements

GHS US labelling

Hazard pictograms (GHS US)





GHS05 GHS06

Signal word (GHS US) : Danger

Hazard statements (GHS US) : Toxic if swallowed.

Harmful in contact with skin.

Causes severe skin burns and eye damage.

Precautionary statements (GHS US) : Do not breathe mist, vapours.

Wash thoroughly after handling

Do not eat, drink or smoke when using this product. Wear eye protection, protective gloves, protective clothing. If swallowed: Immediately call a doctor, a POISON CENTER.

If swallowed: rinse mouth. Do NOT induce vomiting.

If on skin: Wash with plenty of water.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

Immediately call a POISON CENTER, a doctor.
Call a doctor, a POISON CENTER if you feel unwell.
Specific treatment (see First aid measures on this label).

Specific treatment (see supplemental first aid instruction on this label)

Rinse mouth.

Take off contaminated clothing and wash it before reuse.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container to comply with local/regional/national/international regulations..

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures			
Name	Product identifier	%	GHS-US classification
Sodium Hydroxide	(CAS-No.) 1310-73-2	40-70	Acute Tox. 4 (Dermal), H312 Skin Corr. 1A, H314

Safety Data Sheet

Potassium Hydroxide	(CAS-No.) 1310-58-3	3-7	Acute Tox. 3 (Oral), H301
			Skin Corr. 1, H314
			Eye Dam. 1, H318

All hazardous chemicals, as determined by 29 CFR 1910.1200 have been listed. A specific chemical identity and/or percentage of composition has been withheld as a trade secret. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower.

Take victim to a doctor if irritation persists.

First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for

several minutes. Immediately call a POISON CENTER/doctor.

First-aid measures after ingestion : Immediately call a POISON CENTER/doctor. Rinse mouth. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Causes severe skin burns and eye damage.

Symptoms/effects after inhalation : Corrosive to the respiratory tract.

Symptoms/effects after skin contact : Harmful in contact with skin. Caustic burns/corrosion of the skin.

Symptoms/effects after eye contact
: Causes serious eye damage. Permanent eye damage.
Symptoms/effects after ingestion
: Toxic if swallowed. Burns to the gastric/intestinal mucosa.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : ABC powder.

5.2. Special hazards arising from the substance or mixture

Reactivity : Reacts violently with water. Reacts with (some) metals: release of highly flammable gases/vapours

(hydrogen).

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water moderately and if possible collect or

contain it. Use water spray or fog for cooling exposed containers.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Isolate from fire, if possible, without unnecessary risk.

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Protective goggles. Face shield.

Emergency procedures : Keep upwind.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent soil and water pollution.

6.3. Methods and material for containment and cleaning up

For containment : Contain released product, collect/pump into suitable containers.

Methods for cleaning up : Absorb spillage to prevent material damage. Small quantities of liquid spill: neutralize with acid solution.

This material and its container must be disposed of in a safe way, and as per local legislation.

This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safety Data Sheet

Precautions for safe handling : Carry operations in the open/under local exhaust/ventilation or with respiratory protection. Do not

handle until all safety precautions have been read and understood. Use personal protective equipment

as required.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Store in original container. Store in a dry place. Store in a

closed container. Keep cool.

Incompatible products : Strong acids. Incompatible materials : Metals.

Storage area : Keep only in the original container. Store in a dry area. Store in a cool area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Sodium Hydroxide (1310-73-2)		
ACGIH	ACGIH OEL C	2 mg/m³
ACGIH	Remark (ACGIH)	URT, eye, & skin irr
OSHA	OSHA PEL TWA [1]	2 mg/m³

Potassium Hydroxide (1310-58-3)		
ACGIH	ACGIH OEL C	2 mg/m³
ACGIH	Remark (ACGIH)	URT, eve. & skin irr

8.2. Exposure controls

Personal protective equipment

: Face shield. Gloves. Safety glasses. Protective clothing. Use appropriate personal protective equipment when risk assessment indicates this is necessary.









SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear to hazy liquid
Odour : Mild odor
Odour threshold : No data available

рΗ Melting point No data available Freezing point No data available Boiling point No data available Flash point No data available No data available Relative evaporation rate (butylacetate=1) Flammability (solid, gas) No data available Explosive limits No data available Explosive properties No data available No data available Oxidising properties

Relative vapour density at 20 °C No data available Density 1.51 g/ml Solubility Soluble in water. Partition coefficient n-octanol/water (Log Pow) No data available Partition coefficient n-octanol/water (Log Kow) No data available No data available Auto-ignition temperature Decomposition temperature No data available Viscosity No data available Viscosity, kinematic No data available Viscosity, dynamic No data available

VOC content : 0 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapour pressure

Relative density

Reacts violently with water. Reacts with (some) metals: release of highly flammable gases/vapours (hydrogen).

No data available No data available

Safety Data Sheet

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

Reacts violently with water.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

May be corrosive to metals. Strong acids. metals.

10.6. Hazardous decomposition products

May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Drain Away	
LD50 oral rat	214 mg/kg Potassium Hydroxide
LD50 dermal rabbit	1350 mg/kg Sodium Hydroxide

Sodium Hydroxide (1310-73-2)	
LD50 oral rat	4090 mg/kg
LD50 dermal rabbit	1350 mg/kg
ATE CLP (oral)	4090 mg/kg bodyweight
ATE CLP (dermal)	1350 mg/kg bodyweight

Potassium Hydroxide (1310-58-3)	
LD50 oral rat	273 mg/kg (Rat, Oral)
ATE CLP (oral)	273 mg/kg bodyweight

Skin corrosion/irritation : Causes severe skin burns.

pH: 14

Serious eye damage/irritation : Assumed to cause serious eye damage

pH: 14

Respiratory or skin sensitisation : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified

STOT-repeated exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Symptoms/effects after inhalation : Corrosive to the respiratory tract.

Symptoms/effects after skin contact : Harmful in contact with skin. Caustic burns/corrosion of the skin.

Symptoms/effects after eye contact : Causes serious eye damage. Permanent eye damage. Symptoms/effects after ingestion : Toxic if swallowed. Burns to the gastric/intestinal mucosa.

Likely routes of exposure : Skin and eyes contact

SECTION 12: Ecological information

12.1. Toxicity

Potassium Hydroxide (1310-58-3)	
LC50 - Fish [1]	80 mg/l (96 h, Gambusia affinis, Pure substance)

12.2. Persistence and degradability	
Potassium Hydroxide (1310-58-3)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

Safety Data Sheet

BOD (% of ThOD) Not applicable

Bioaccumulative potential 12.3.

Potassium Hydroxide (1310-58-3)

Bioaccumulative potential Not bioaccumulative

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations

: Dispose of contents/container to comply with local/regional/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport document description (DOT)

UN-No.(DOT)

Proper Shipping Name (DOT)

Class (DOT) Hazard labels (DOT) UN3266 Corrosive liquid, basic, inorganic, n.o.s. (sodium hydroxide, potassium hydroxide), 8, II

UN3266

Corrosive liquid, basic, inorganic, n.o.s.

8 - Class 8 - Corrosive material 49 CFR 173.136

8 - Corrosive



B2,IB2,T11,TP2,TP27

154

: 1L

: 30 L

Packing group (DOT) II - Medium Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) 202

DOT Packaging Bulk (49 CFR 173.xxx) 242 G - Identifies PSN requiring a technical name

DOT Symbols

DOT Special Provisions (49 CFR 172.102)

DOT Packaging Exceptions (49 CFR

173.xxx)

DOT Quantity Limitations Passenger

aircraft/rail (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft

only (49 CFR 175.75)

DOT Vessel Stowage Location

DOT Vessel Stowage Other

: B : 40 - Stow "clear of living guarters",52 - Stow "separated from" acids

Additional information

Other information

: When transported by ground, this product may be eligible to be shipped as a Limited Quantity utilizing the exception found at 49 CFR 173.154. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may be required.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Sodium Hydroxide	(1310-73-2)	CERCLA RQ1000 lb
Potassium Hydroxide	(1310-58-3)	CERCLA RQ1000 lb

Safety Data Sheet

MARNING

This product can expose you to cadmium (non-pyrophoric), which is known to the State of California to cause cancer and birth defects or other reporductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.


NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA fire hazard : 0 - Materials that will not burn under typical fire conditions, including intrinsically noncombustible

materials such as concrete, stone, and sand.

NFPA reactivity : 1 - Materials that in themselves are normally stable but can become unstable at elevated

temperatures and pressures.



Issue Date 2/16/2022 Revision Date 3/19/2018 version 1.2

Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.