Blizzard 2010

### **SECTION I - IDENTIFICATION**

PRODUCT IDENTIFIER: Blizzard 2010

**PRODUCT CODE: ABZ534** 

RECOMMENDED USE: Snow Repellent RESTRICTIONS ON USE: None Known COMPANY NAME: Pro-Line Industrial Product

COMPANY ADDRESS: 723 W. University #110-428 Georgetown, TX 78626.

**COMPANY PHONE:** (800) 263-9436

EMERGENCY PHONE: 800-424-9300 Chemtrec

### SECTION II - HAZARDS IDENTIFICATION

CLASSIFICATION: Flammable Aerosol: Category 1

Gases Under Pressure: Liquefied Gas

Skin Irritant: Category 2

Reproductive Toxicity: Category 2

Specific Target Organ Toxicity (Single Exposure): Category 3 Specific Target Organ Toxicity (Repeated Exposure): Category 2

Aspiration Hazard

HAZARD STATEMENT(S): DANGER: Extremely Flammable Aerosol. Contains gas under pressure: May explode if heated. Causes skin irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs (central nervous system, kidney, peripheral nervous system, brain, lungs and reproductive system) through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: N/A

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves, protective clothing, eye protection and face protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. Take off contaminated clothing and wash before reuse. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Do not breathe fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and national regulations.

### **SYMBOL:**









## HAZARDS NOT OTHERWISE CLASSIFIED: N/A

### SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Hexane	110-54-3	30-60%
N-Butane	106-97-8	10-30%
Heptane	142-82-5	10-30%
Propane	74-98-6	5-15%
Naphtha (petroleum), hydrotreated light	64742-49-0	5-15%
Distillates (petroleum), light distillate hydrotreating process, low-	68410-97-9	5-15%
hoiling		

Blizzard 2010

#### **SECTION IV - FIRST AID MEASURES**

**EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

**INGESTION**: If swallowed: Rinse mouth. Do NOT induce vomiting. Get medical advice or attention.

**INHALATION**: Move to fresh air. If breathing is difficult or unconscious, administer oxygen. If not breathing administer artificial respiration. Seek medical attention if irritation persists.

**SKIN:** Wash skin thoroughly with soap and water. Remove contaminated clothing and shoes, launder before reuse. If irritation persists seek medical attention.

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision

Skin: defatting and dermatitis

Inhalation: Anesthetic, irritation, Central Nervous System depression Oral: abdominal irritation, nausea, vomiting, diarrhea, and aspiration risk

**CHRONIC HEALTH HAZARDS:** Excessive exposure may result in peripheral neuropathies due to n-hexane. Symptoms would be sensory numbness and possible motor weakness in extremeties.

NOTE TO PHYSICIAN: If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

#### **SECTION V - FIRE-FIGHTING MEASURES**

**EXTINGUISHING MEDIA:** Dry chemical, carbon dioxide, foam, and water spray or fog.

UNSUITABLE EXTINGUISHING MEDIA: Water spray/stream.

**SPECIAL FIRE FIGHTING PROCEDURES:** Wear full protective clothing and NIOSH approved SCBA with full facepiece operated in positive pressure or pressure demand. Use water mist to keep material cool in fire situations.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** EXTREMELY FLAMMABLE. Contents under pressure. Exposure to temperatures above 120 F may cause bursting. Keep away from heat, sparks, open flames and other sources of ignition.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon.

## **SECTION VI – ACCIDENTAL RELEASE MEASURES**

**PERSONAL PROTECTIVE EQUIPMENT:** Refer to section VIII for proper Personal Protective Equipment.

**SPILL:** Absorb with non-combustible material like vermiculite, sand or earth and rinse with small amount of soapy water. Do not allow to drain into sewers or storm drains. Dispose of in accordance with local, state and federal regulations.

**WASTE DISPOSAL:** Dispose of in accordance with local, State and Federal regulations. Do not puncture or incinerate container. Do not reuse empty container. Wrap container and place in trash collection.

RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

## **SECTION VII – HANDLING AND STORAGE**

**HANDLING AND STORAGE:** Wear appropriate protective equipment. Avoid contact with skin, eyes and clothing. Do not inhale mist or vapor. Store in cool, dry, ventilated area. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

OTHER PRECAUTIONS: Keep out of the reach of children.

**INCOMPATIBILITY:** Strong oxidizing agents, strong reducing agents.

## SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Hexane	500 ppm	50 ppm
N-Butane	Not Established	1000 ppm
Heptane	500 ppm	400 ppm
Propane	1000 ppm	1000 ppm
Naphtha (petroleum), hydrotreated light	Not Established	247 ppm
Distillates (petroleum), light distillate	Not Established	200 ppm
hydrotreating process, low-boiling		

Blizzard 2010

**ENGINEERING CONTROLS / VENTILATION:** Material is heavier than air. Material may concentrate in low lying areas. Normal, forced ventilation required to meet TLV requirements. Local exhaust ventilation is generally preferred.

**RESPIRATORY PROTECTION:** If exposure levels are exceeded then organic vapor cartridge respirator or SCBA will be needed.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses and chemical resistant gloves

**ADDITIONAL MEASURES:** Wear protective clothing to prevent repeated or prolonged contact with product. Wash hands thoroughly after handling.

### **SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES**

**APPEARANCE:** Clear, colorless spray

**ODOR:** Solvent odor **ODOR THRESHOLD:** N/D

pH: N/D

MELTING POINT/FREEZING POINT: N/D

INITIAL BOILING POINT AND BOILING RANGE: N/D

FLASH POINT: N/D

**EVAPORATION RATE: N/D** 

**FLAMMABILITY(solid/gas):** Extremely Flammable Aerosol **UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:** 

LOWER FLAMMABILITY LIMIT: N/D UPPER FLAMMABILITY LIMIT: N/D EXPLOSIVE LIMIT LOWER (%): N/D EXPLOISVE LIMIT UPPER (%): N/D VAPOR PRESSURE (mm Hg): N/D VAPOR DENSITY (AIR=1): N/D

**RELATIVE DENSITY (H2O=1):** 0.68 - 0.71

**SOLUBILITY(IES):** N/D

PARTITION COEFFICIENT: n-OCTANOL/WATER (Kow): N/D

**AUTOIGNITION TEMPERATURE:** N/D **DECOMPOSITION TEMPERATURE:** N/D

VISCOSITY: N/D

## **SECTION X – STABILITY AND REACTIVITY**

REACTIVITY: None known.
CHEMICAL STABILITY: Stable

POSSIBLE HAZARDOUS REACTIONS: None Known

**CONDITIONS TO AVOID:** Excess heat, open flame, sparks, electric equipment, ignition sources, and incompatible materials.

**INCOMPATIBLE MATERIALS:** Strong oxidizing agents, strong reducing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon, various hydrocarbons.

#### SECTION XI - TOXICOLOGICAL INFORMATION

**TOXICOLOGICAL INFORMATION:** Hexane (110-54-3) LD<sub>50</sub> (Oral, Rat) > 5000 mg/kg; LD<sub>50</sub> (Dermal, Rabbit) > 2000 mg/kg;

LC<sub>50</sub> (Inhalation, Rat, 4hrs) > 3367 ppm **n-Butane** (106-97-8) LC50 (Inhalation, Rat, 4hr) 30957 mg/m3 **Heptane** (142-82-5)

LC<sub>50</sub> (Vapors, Mice) 1600 ppm **Propane** (74-98-6) LC50 (Inhalation, Rat, 4hr) 658 mg/l

ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin

**EYES:** May cause irritation, pain, redness, tearing, swelling.

**INGESTION:** May cause gastrointestinal irritation, nausea, diarrhea, vomiting, aspiration hazard.

**INHALATION:** May cause irritation to the respiratory tract, dizziness, headaches, drowsiness, unconsciousness.

**SKIN:** Irritation likely, redness and pain. May cause localized defatting, blistering with prolonged skin contact. May be absorbed through the skin.

**MEDICAL CONDITION AGGRAVATED:** Excessive exposure will aggravate pre-existing disorders of eyes, skin, respiratory, liver, kidney, cardiovascular system, pulmonary illnesses, or central nervous system.

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision

Skin: defatting and dermatitis

Inhalation: Anesthetic, irritation, Central Nervous System depression Oral: abdominal irritation, nausea, vomiting, diarrhea, and aspiration risk

Blizzard 2010

CHRONIC HEALTH HAZARDS: Excessive exposure may result in peripheral neuropathies due to n-hexane. Symptoms would be

sensory numbness and possible motor weakness in extremeties.

CARCINOGENICITY: OSHA: No ACGIH: No NTP: No IARC: No OTHER: CA Prop 65

### **SECTION XII - ECOLOGICAL INFORMATION**

**ECOTOXICITY:** This material is toxic to aquatic life.

PERSISTENCE AND DEGRADABILITY: This product is biodegradable.

BIOACCUMULATIVE POTENTIAL: Components in this mixture can bioaccumulate in aquatic organisms.

**MOBILITY IN SOIL: N/D** 

**OTHER ADVERSE EFFECTS:** None Known

## **SECTION XIII - DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL:** Dispose of in accordance with local, State and Federal regulations. Do not puncture or incinerate container. Do not reuse empty container. Wrap container and place in trash collection.

RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

### **SECTION XIV - TRANSPORT INFORMATION**

**PROPER SHIPPING NAME:** Aerosols, Ltd. Qty.

**HAZARD CLASS/DIVISION: 2.1** 

UN/NA NUMBER: UN 1950

PACKING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, flammable

**HAZARD CLASS/DIVISION: 2.1** 

UN/NA NUMBER: UN 1950

PACKING GROUP: N/A

SHIPPING BY WATER: VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.1 UN/NA NUMBER: UN 1950 PACKING GROUP: N/A

**ENVIRONMENTAL HAZARDS WATER:** Marine Pollutant

# **SECTION XV - REGULATORY INFORMATION**

TSCA STATUS: All Chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): Hexane (110-54-3) Reportable Ouantity = 5,000 lbs

SARA 311/312 HAZARD CATEGORIES: Acute Health, Chronic Health, Fire, Pressure.

**SARA 313 REPORTABLE INGREDIENTS: n-Hexane** (110-54-3)

STATE REGULATIONS: California Proposition 65: This product can expose you to chemicals including benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="https://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>. Hexane (110-54-3) is listed on the following State Hazardous Substance Inventories, Right-to-Know lists and/or Air Quality/Air Pollutants lists: CA, NJ, NY, NC, PA, RI, WI.

INTERNATIONAL REGULATIONS: All components of this product are on the Canadian DSL list.

**VOLATILE ORGANIC COMPOUNDS (VOC): 96%** 

NFPA HEALTH: 2
NFPA FLAMMABILITY: 3
NFPA REACTIVITY: 0
HMIS HEALTH: 2
HMIS FLAMMABILITY: 3
HMIS REACTIVITY: 0

NFPA OTHER: None HMIS PROTECTION: B

Blizzard 2010

### **SECTION XVI - OTHER INFORMATION**

**DATE PREPARED:** 08/15/2014 **REVISION DATE:** 01/31/2022

N/A = Not Applicable; N/D = Not Determined

**DISCLAIMER:** To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.