



Industrial Products



Quick Aluminum

DESCRIPTION: QUICK ALUMINUM is an aluminum reinforced epoxy putty. QUICK ALUMINUM is a hand kneadable, non rusting epoxy that hardens to an aluminum-like substance. QUICK ALUMINUM dries in minutes, with a full cure in only 1 hour. QUICK ALUMINUM is a specialty epoxy which bonds tenaciously to most metals. After final cure, QUICK ALUMINUM can be drilled, tapped, machined, ground or filed. QUICK ALUMINUM will not shrink or pull away, and contains no harsh solvents. QUICK ALUMINUM is quick, easy to use, economical and fool proof, with no liquid mixing or measuring needed. Shear tensile strength on aluminum (1"x 1"x 1/16") lbs 400 - 600.

ADVANTAGES: 1) Base epoxy and curing agent wrapped in one tube. 2) Cures in only 1 hour. 3) Cut off only amount desired, making product very economical to use. 4) Soft putty texture makes for easy kneading. 5) No pre mixing or measuring of liquids required. 6) Non fuming formulation allows for use in any area. 7) Bonds to most metals with little preparation required. 8) Chemically resistant to hydrocarbons, ketones, alcohols, esters, halocarbons, aqueous salt solutions and dilute acids and bases.

AREAS OF USE: Repairs to - gutters, storm doors, windows, shower frames, aluminum siding, air conditioning units, machine parts, wheels and much more.



SPECIFICATIONS:

Classification	Epoxy putty tube
Color	Gray
Working life (minutes)	5 - 7
Cure time (minutes)	60
Shrinkage	<1%
Electrical resistance (megohms)	30,000
Dielectric strength (volts/mil)	300

Certified 100% Women-Owned Small Business

Dedicated to Integrity • Reliability • Quality Products • Friendly Service

Our Products are Made in the USA and we Proudly Support Veteran Endowments