

Quick Wood

Wood Repair

QUICK WOOD is a hand mixable epoxy putty specially formulated to repair and rebuild wood quickly and easily. QUICK WOOD has a curing agent encapsulated in a contrasting color base material. When mixed together, the materials combine to form a polymer compound that cures to the same density and light brown color of most woods. QUICK WOOD becomes an integral part of the item being prepared. QUICK WOOD may be used for exterior or interior applications, contains no solvents, and will not shrink, crack, rot or pull away. After final cure, QUICK WOOD can be drilled, tapped, machined, sanded, filed or stained.

Areas of Use:

- tables
- knot holes
- screw holes

- dry rot
- window and door frames
- and much more

Advantages:

- 1. Easy to use, simply twist or cut off required amount of product, knead with fingers to a uniform color and apply to surface to be repaired.
- 2. QUICK WOOD has a 15 to 25 minute work life and hardens in 60 minutes to form a tenacious bond.
- 3. QUICK WOOD fully cures in 24 hours.

Directions for use:

For best results, clean and roughen bond area prior to application. Twist or cut off required amount of product. To mix, knead with fingers to a uniform colors. Apply to surface to be repaired (within two minutes of mixing). Force into any cracks or holes to be filled and strike off excess material. For a smooth appearance of the cured compound, hand rub with water or a damp cloth prior to hardening. Remove excess material before hardening begins. Quick wood has a 15 to 25 minute work life and hardens in 60 minutes to form a tenacious bond.

Product #BQW9194



Specifications:

Classification Color	Epoxy putty Light Brown
Working Life(minutes)	15-25
Shrinkage	< 1%
Cure time (hours)	24
Dielectric strength (volts/mil)	300
Electrical resistance (megohms)	30,000

Certified 100% Women-Owned Small Business

Dedicated to Integrity • Reliability • Quality Products • Friendly Service

Our Products are Made in the USA and we Proudly Support Veteran Endowments